

DEDICATED
MACHINE
SERIES

专用机系列



D300N 粘合机
Fusing Machine



1、本机配备大功率电机，与相配减速机合装，粘合速度加倍，极大的提高了工作效率

Equipped With Large-power Motor To Match With The Reducer; Improved Bonding Speed To Significantly Increase Working Efficiency

2、本机采用上下铝材加热板，传热效率高，不同机型，配备6-9块加热板，节能减排

Upper/lower Aluminum Heating Plate To Ensure High Heating Efficiency; Varied Models With 6-9 Heating Plates To Ensure Energy Saving And Reduce Emission

3、自停功能，当设备温度低于所设定的温度时，设备才会完全停机

Automatic Stop Function To Ensure Full Stop Only When The Desired Temperature Is Reached

4、科学设计，精密的进料口构造，使粘合产品从料口平整进入

Scientific Design And Precise Feed Inlet Structure To Facilitate Bonding Products Smoothly Entering Into Feed Inlet

型号 Model	电压 Voltage (V)	加热率 Heating Rate (Kw)	电机 Motor (W)	工作温度(°C) Operating Temperature	粘合力 Adhesive Pressure (Kg/cm²)	氟带速度 Fluoro Belt Speed (M/min)	粘宽度 Binding Width (mm)	体积 Meas (cm)	重量 Weight (Kg)
D300N	220	4.8	300	50-220	0-4	0-10	300	85×102×69	160
D400N	220	5.1	300	50-220	0-4	0-10	400	90×102×68	180
D450N	220	5.5	300	50-220	0-4	0-10	450	98×103×67	190
D500N	220	6	400	50-220	0-4	0-10	500	103×103×67	200
D600N	220/380	7	400	50-220	0-4	0-10	600	113×103×67	220
D700N	220/380	7.5	400	50-220	0-4	0-10	700	125×102×70	240
D800N	220/380	8.5	600	50-220	0-4	0-10	800	133×110×70	260
D900N	380	9.8	600	50-220	0-4	0-10	900	143×116×70	280
D1000N	380	12	700	50-220	0-4	0-10	1000	155×130×68	320
D1050N	380	12	700	50-220	0-4	0-10	1050	158×135×68	340
D1200N	380	13.5	800	50-220	0-4	0-10	1200	173×145×72	450